

ES1010

1U 48-port 1GbE (PoE) Access Switch



The Celestica ES1010 provides **48x 1000Base-T and 4x 25GbE SFP28 ports in support of enterprise access, edge and data center applications.**

ES1010 includes high-reliability features such as redundant fixed fans and hot swappable power supplies. The platform is available in both forward and reverse airflow configurations with optional 90W per port PoE++ support.

The ES1010 is ideal for:

- Enterprise Edge / Access / Campus Aggregation
- SD-Branch / SD-WAN / SASE
- IoT
- DCN Management Switches

FEATURES

Broadcom TD3.X2 switch chipset
148Gbps non-blocking switching capacity
Intel Denverton x86 CPU, 4C / 8C at 2.1GHz / 2.2GHz
Memory: DDR4 16GB or more (32GB), 64GB up to 256GB M.2 SSD
Encryption: 256b MACsec
Optional: IEEE 1588 and SyncE timing support
48-port 1000Base-T (RJ45)
Optional: IEEE 802.3 af / at / bt, Type 4, Class 8 enabled RJ45 ports, persistent PoE
4 ports 1GbE / 10GbE / 25GbE (SFP28)
RJ45 console and Combo / SFP OOB Ethernet management ports
2x USB 3.0 Type A interfaces
1+1 hot swappable AC PSUs with 0:1 / 1:1 mode of operations
2+1 fixed fans
ROHS Compliant



Enterprise-Class Quality. Cloud Economics.

LAYER TWO HARDWARE SUPPORTED

VLAN Learning, Shared VLAN switching,
VLAN double tagging

HW based address learning, MAC address aging
(except static MAC address)

Class based learning

IEEE 802.3 packet sizes (64 bytes to 1522 bytes),
Jumbo packet up to 12,288 bytes

Multicast

Spanning tree

Storm Control

IEEE 802.3ad LAG

Ingress / Egress mirroring

DSCP

LAYER THREE HARDWARE SUPPORTED

IPv4, IPv6

VRF

IP Multicast

IPv6 Tunneling

GRE Tunneling

Server Virtualization / VN-Tag / VEPA / IEEE 802.1Qbh

VxLAN

RIOT

Tunnel Encap / Decap

Resilient Hashing

Pre-Classification Content Aware Processor (VFP)

Content Aware Processing (IFP / EFP)

Port Security (IEEE 802.1x)

BroadShield™ DoS Attack Prevention

QoS

Priority Flow Control (PFC) IEEE 802.1bb

Flexible Counters

Network Time Sync

MIB – RFC 2613, 2819, 1213, 2836, 1643, 1493;
IEEE 802.3u

CMICx

Ethernet OAM

Flow Control

Bridge Port Extender IEEE 802.1Qbg, 802.1BR

Energy Efficient Ethernet (EEE)

PHYSICAL DIMENSIONS

Height: 43.4 mm (1U)

Width: 438.2 mm

Depth: 371.6 mm

ENVIRONMENTAL : OPERATING

Temperature: 0°C to 45°C @ 900m

Humidity: 5%~85% (Upper limits per ASHRAE A3)

Altitude: 3050m maximum. Derate ambient 1C /
175m above 900m

APPROVALS

EMC: Class B- USA, Canada, Europe, Japan, China

Safety: UL / CSA / IEC / EN 60950-1 / 62368-1

PSU: CE, FCC, CCC, KC, TUV, UL / cUL, BIS and BSMI

ORDER INFORMATION

R4048-F90LA-A1: ES1010-48C, 1U, 48x1GbE,
COMe 4C/16GB-DDR/64GB-SSD (F2B)

R4048-F91LA-A1: ES1010-48C, 1U, 48x1GbE,
COMe 4C/16GB-DDR/64GB-SSD (B2F)

R4048-F90L9-A1: ES1010-48CP, 1U, 48x1GbE,
POE++, COMe 4C/16GB-DDR/64GB-SSD (F2B)

R4048-F91L9-A1: ES1010-48CP, 1U, 48x1GbE,
POE++, COMe 4C/16GB-DDR/64GB-SSD (B2F)

*Note: All specifications and figures are subject to change
without prior notice.*